SMD CONTACT SPRINGS
FCB-01CX2030040B-YY-SMD

SMD contact springs are ideal for automatic assembly on printed circuit boards. They are soldered by the standard-reflow-soldering process.

The standard basic material used for SMD contact springs is copper beryllium (CuBe). However, other materials can also be supplied.

As standard, SMD springs are gold-plated (AU). They can be supplied in a wide range of dimensions and shapes.

- Ideal for automatic assembly
- Standard basíc material: CuBe
- Standard plating: AU
- Available in different dimensions and types
- Almost unlimited working life

RoHS ✓ REACH ✓ REEL

PRODUCT SPECIFICATIONS

PROPERTY		VALUE / TOLERANCE
Thickness		0,1 mm
Width		2,0 mm ± 0,2
Length		3,0 mm ± 0,2
Height		4,0 mm ± 0,2
Basic material		Copper beryllium (CuBe)
Plating	Barrier layer NI Outer layer AU	1µm – 2µm 0,025µm – 0,075µm



DIMENSIONS (mm)







SMD CONTACT SPRINGS
FCB-01CX2030040B-YY-SMD

RECOMMENDED RESERVED AREA ON THE PCB (mm)



RECOMMENDED PAD FOR THE PCB (mm)



DISCLAIMER

This is only a recommendation based on information available to mtc at the time of printing. Actual land pattern can be significantly different due to various materials and processes used in PCB assembly. mtc makes no representation or warranty of performance based on the recommended land pattern.

BUILDING AN ITEM NUMBER

FCB-01CX2030040B-YY-SMD

Contact Spring	
Type number	
G/AU	Gold-plated
S/SN	Tin-plated
A/AG	Silver-plated
Dimensions	
Copper beryllium	
SMD type	

Standard options

FORCE DEFLECTION DIAGRAM*



Total Compression Distance(mm)	0.80mm	
Displacement (mm)	Loading force(g) Down direction	Loading force(g) UP direction
0.00	0	0
0.03	2	2
0.07	9	5
0.11	16	9
0.15	45	25
0.19	64	37
0.24	88	54
0.28	122	65
0.32	136	70
0.36	154	78
0.40	166	88
0.44	182	94
0.49	188	101
0.53	204	105
0.57	204	114
0.61	205	119
0.66	214	130
0.70	218	147
0.74	220	168
0.78	222	191
0.80	220	220

NOTE | * Only valid for gold-plated version

SMD CONTACT SPRINGS
FCB-01CX2030040B-YY-SMD

PACKING SPECIFICATION – TAPE AND REEL (mm)



	W	A_0	B_0	K_0	P	F	E	D_0	P_0	P_0	T
	12,00	2,20	3,20	4,15	8,00	5,50	1,75	Ø 1,50	4,00	2,00	0,35
Tolerance	± 0,30	± 0,10	± 0,10	± 0,10	± 0,10	± 0,05	± 0,10	+ 0,10 - 0,00	± 0,10	± 0,05	± 0,05

- 10 sprocket hole pitch cumulative tolerance ± 0,20 mm.
- Carrier camber not to exceed 1 mm in 250 mm.
- A0 and B0 measured on a plane 0,3 mm above the bottom of the pocket.
- K0 measured from a plane on the inside bottom of the pocket to the top surface of the carrier.
- All dimensions meet EIA-481-B requirements.
- Material: Clear non anti-static polystyrene.
- Component load per 13'' reel: 2.000 pcs.

Modifications and errors excepted. The information and statements herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verifications and testings to determine the suitability for their own particular purpose of any information or products referred to herein.